

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claims 1-20 (Cancelled)

21. (Currently Amended) An apparatus for an amputee who has a residual limb, comprising:

a flexible liner adapted to cover a portion of the residual limb;

only a single socket, wherein the socket has a cavity to receive the liner and residual limb such that there is a space between the socket and the liner when received in the cavity; and

a vacuum source in fluid communication with the space between the liner and the residual limb when the liner and residual limb are received in the cavity;

wherein the apparatus includes no tubing for insertion between the liner and the residual limb for removing air at an interface between the liner and the residual limb, and wherein the flexible liner comprises a non-porous material adapted to cover the portion of the residual limb received in the cavity.

22. (Previously Presented) The apparatus of claim 21, wherein the socket is substantially rigid.

23. (Previously Presented) The apparatus of claim 21, wherein the socket has a limb opening through which the residual limb may pass and has a vacuum opening through which the vacuum source and the cavity fluidly communicate.

24. (Previously Presented) The apparatus of claim 21, further comprising a vacuum valve between the vacuum source and the cavity.
25. (Previously Presented) The apparatus of claim 24, wherein the vacuum valve is connected to the socket.
26. (Previously Presented) The apparatus of claim 21, wherein the vacuum source is configured to evacuate air from the cavity to draw the limb toward the socket.
27. (Previously Presented) The apparatus of claim 21, wherein the vacuum source comprises a mechanical pump.
28. (Previously Presented) The apparatus of claims 21, wherein the vacuum source comprises a motor-driven pump.
29. (Previously Presented) The apparatus of claim 28, further comprising a power source, wherein power source is connected to the motor-driven pump.
30. (Previously Presented) The apparatus of claim 29, wherein the power source comprises a battery.
31. (Previously Presented) The apparatus of claim 21, further comprising a regulator for controlling the vacuum source.
32. (Previously Presented) The apparatus of claim 29, further comprising a regulator connected to the power source for controlling the vacuum source.
33. (Previously Presented) The apparatus of claim 21, further comprising a prosthetic limb member that includes one of a portion of a prosthetic leg or prosthetic arm, wherein the prosthetic limb member is connected to the socket.
34. (Previously Presented) The apparatus of claim 21, further comprising a seal member adapted to be between the socket and the residual limb to reduce air leakage into the space.

35. (Currently Amended) An apparatus for an amputee who has a residual limb comprising:

a flexible liner adapted to cover a portion of the residual limb;

only a single socket, wherein the socket has a cavity to receive the liner and residual limb;

a motor-driven vacuum pump in fluid communication with the space when the liner and residual limb are received in the cavity; and

a battery for powering the motor-driven vacuum pump;

wherein the apparatus includes no tubing for insertion between the liner, and wherein the flexible liner comprises a non-porous material adapted to cover the portion of the residual limb received in the cavity.

36. (Currently Amended) A method for securing a portion of the residual limb of an amputee to a prosthesis, comprising the steps of:

providing only a single prosthetic socket having a cavity, a flexible liner including a non-porous material, and a vacuum source;

inserting a portion of a residual limb into the flexible liner and into the cavity of the socket such that the non-porous material covers the portion of the limb inserted into the cavity;

removing air between the residual limb and the socket using the vacuum source to force the residual limb and the socket together; and

not inserting tubing between the residual limb and the flexible liner to remove air at an interface between the residual limb and the flexible liner.

37. (Currently Amended) The method of claim 36, further comprising the step[[s]] of controlling the vacuum source to continue to force the residual limb and socket together.

38. (Previously Presented) The method of claim 36, wherein the vacuum source comprises a motor-driven pump powered by the battery.

39. (New) The method of claim 34 wherein the seal member is formed from the same non-porous material as the non-porous portion of the liner.

40. (New) The method of claim 21 wherein the liner further comprises a porous sleeve disposed over an outer surface of the non-porous portion of the liner.